

Universal Smartcard Module



A Flexible Contactless Card Approach

The Universal Smartcard Module (USM) is a high performance in-field re-programmable contactless smart card reader designed for use by system integrators in the public transport industry and other markets where performance and cost are important. A high speed ARM9 micro-controller controls all the major functions to provide a flexible development platform for developers while providing high data throughput.

The dual contactless interface supports the complete Customer Media family as defined by ITSO™ and includes MIFARE®, DESFire®, Jewel™, FeliCa® and Calypso®

Four integral ISO7816 compatible SAM slots are provided to allow the secure storage of encryption keys and to allow several schemes to co-exist on the same platform.

The module can be easily connected to a PC or other host systems using USB, TCP/IP or RS232 interface.

The module is equipped with an integrated real time clock (RTC) which is independently powered by a Lithium coin cell.

Applications:

- ❖ Ticket Vending Machines (TVM)
- ❖ Point of Service Terminals (POST)
- ❖ Platform Ticket Validators
- ❖ Transport Gates and Turnstiles
- ❖ Value Load Terminals (VLT)



Universal Smartcard Module



Features

- ❖ Field upgradeable reader firmware
- ❖ Small form factor
- ❖ External dual ISO14443 antenna with LED's (x3) and buzzer
- ❖ Supports all Customer Media as defined by ITSO™
- ❖ NFC ready - FeliCa® compatible
- ❖ Multiple connections to external systems using USB2.0, RS232 (x2) or Ethernet (10/100Mbps)
- ❖ Contactless EMV ready

GIS can supply either full customisation or a software development platform for in-house development.
Please contact GIS for further details.



Technical Specification

- ❖ 32-bit ARM9 based single chip microcontroller with variable clock speed up to 180MHz
- ❖ 512KBytes internal Flash memory (program memory) / 32KBytes internal RAM
- ❖ 64MBytes of external DRAM (*Optional 128MB)
- ❖ 256MBytes of external NAND Flash
- ❖ 8KBytes of non removable FeRAM memory
- ❖ 2GB of removable Flash memory using Transflash technology
- ❖ Real Time Clock with independent Lithium coin cell
- ❖ Keyboard interface (4 x 3 n/o switches)
- ❖ Host interface with USB 2.0 (host and slave), RS232 or 10/100Mbps Ethernet
- ❖ Dual Contactless Smartcard interface compatible with ISO14443-A/B and NFC
- ❖ Reading range up to 5cm
- ❖ Quad SAM: ISO7816 ID000 - 3V or 5V
- ❖ 14 Independent I/O signals
- ❖ Input voltage variable from 5.5Vdc to 32Vdc
- ❖ LCD module (x2) expansion
- ❖ Windows CE capable

General Information

Weight: 200 gm

Dimensions: 130 x 85 mm

Operating Environment: -10°C to +60°C ambient, 10 to 90% relative humidity (non-condensing)

Transit and Storage: -20°C to +70°C ambient, 5 to 95% relative humidity (non-condensing)

Standards and Approvals

CE: EN61000-6-1:2001, EN61000-6-3:2001, EN60950:2000, EN300 330-1 V1.3.1, EN300 330-2 V1.1.1, EN301 489-3



Specifications are subject to change without notice - April 2010

MIFARE is a trademark of NXP Semiconductors

FeliCa is the contactless IC card technology developed by Sony Corporation



General Information Systems Ltd

Unit 2, The Woodlands, Barton Road, Haslingfield, Cambs CB23 1LW, UK

Tel.: +44 (0) 1223 873333

Fax.: +44 (0) 1223 870303

Http://www.gis.co.uk - Email: info@gis.co.uk